



# Comline CO 10W40

## 10W-40

### Universal Motor oil

#### Description:

Comline CO 10W40 is a engine oil recommended for petrol and diesel engines. Because of the high viscosity index, the oil ensures an excellent cold start as well as an excellent lubricating film with high temperatures.

Comline CO 10W40 takes care of trouble free functioning of the engine, because of the chosen additive package. The oil may help reduce fuel consumption as well as reducing emission levels. Due to the unique formulation a low evaporation under severe operating conditions is guaranteed.

In addition, Comline CO 10W40 gives optimum protection against wear and has strong anti - corrosion and anti-foam characteristics as well as a high resistance against oxidation. Together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine.

#### Performance level:

API SL/CF  
ACEA A3/B3  
ACEA A3/B4 (04)  
VW 500.00/505.00 (10W)  
MB 229.1

*10W-40: Synthetic based*

#### Typical values

#### 10W-40

Density 20°C	Kg/L	0.860
Viscosity 100°C	cSt	14.8
Viscosity 40°C	cSt	99.1
Viscosity -15°C	cP	-
Viscosity -20°C	cP	-
Viscosity -25°C	cP	<7000
Viscosity Index		156
Flash point COC	°C	>200
Pour point	°C	<-36
Sulphated ash	Wt%	1.0

THIS SHEET CONTAINS RECOMMENDATIONS OR SUGGESTIONS ON PROPERTIES AND POSSIBLE APPLICATIONS OF COMLINE PRODUCTS. BECAUSE OF CONTINUOUS PRODUCT RESEARCH AND DEVELOPMENT, THE INFORMATION IN THIS DOCUMENT CAN BE CHANGED AT ALL TIMES, WITHOUT FOREGOING NOTICE. THE ANALYTICAL INFORMATION IN THIS DOCUMENT CONSISTS OF TYPICAL VALUES. ALTHOUGH THE TEXT HAS BEEN REDACTED WITH GREAT CAREFULNESS, THE AUTHOR WILL NOT ACCEPT ANY LIABILITY FOR DAMAGES CAUSED BY INCOMPLETENESS AND/OR INCORRECTNESS OF THE TEXT. THE READER IS ADVISED TO MAKE THE FINAL PRODUCT CHOICE IN DIALOGUE WITH THE SUPPLIER.